



Indoor/Outdoor Current Transformer

Model JCR-0W – 600V, 10kV BIL, 100 - 1000A

Window Diameter 2.00"



APPLICATION

Designed for both indoor and outdoor service. Suitable for operating meters and instruments, on both single-phase two-wire circuits and polyphase circuits.

WEIGHT

(approximate)
Transformer,

Low Base 4.5 lbs
High Base 5.0 lbs

REFERENCE DRAWINGS

Outline 0121C36111

INSULATION LEVEL

0.6kV; BIL 10kV full wave.

FREQUENCY

50-60 Hz

Current Ratio (Amps) Pri : Sec	ANSI Accuracy Class, 60Hz Burden Per ANSI 0.3 B0.2	Window Size (inside diameter)	Continuous Thermal Current Rating Factor		Catalog Number Without Base	
			@30°C Amb.	@55°C Amb.	With Secondary Hardware and Cover	Without Secondary Hardware and Cover
250:5	100:2 to 1000:20	2.0"	4.0	3.0	750X134608	750X134611
					With Low Base	
250:5	100:2 to 1000:20	2.0"	4.0	3.0	750X134609	750X134612
					With High Base	
250:5	100:2 to 1000:20	2.0"	4.0	3.0	750X134610	750X134613

